



## PRO|EDGE Z201DU

### Display & DVI ZERO CLIENT

#### An ideal solution

for meeting VDI demands in multiple industries.

I-O Corporation's flagship product, Pro|Edge Z201DU is a high-performing solution that was specifically designed to help your company meet its virtual desktop infrastructure needs. This product, which works best in an established VMware® environment, provides users with ready-access to a familiar virtual desktop anytime, anywhere, and also offers dual-monitor support to help them increase their productivity. Moreover, it features the **Tera2321 PC-over-IP (PCoIP) portal processor**, allowing for greater efficiency, performance and security with cloud computing. Plus, it offers one Display port and one DVI port support and six USB ports.

This solution is an excellent choice for meeting a wide variety of VDI end user and business needs in education, financial services, government, healthcare and any other industry or environment where PCoIP Zero clients are required.

For more information or to request a 30-day free trial, visit [www.iocorp.com](http://www.iocorp.com) or call **(800-871-9998)**



### Benefits

#### HIGH-PERFORMING SOLUTION:

A reliable solution that offers a high processing speed and high resolution.

#### GREATLY INCREASES NETWORK SECURITY:

Securely delivers applications to end users in a cloud computing environment.

#### PROVIDES USERS WITH A FAMILIAR DESKTOP EXPERIENCE:

Enables users to access their desktop anytime, anywhere.

#### EASY TO DEPLOY, MANAGE AND USE:

Can be easily and seamlessly integrated into an existing VMware® infrastructure. No configuration required. Moreover, the solution greatly reduces the need to manage images, firmware and settings.

#### LONG LIFE EXPECTANCY:

Minimal space requirements. Durable solution with fan-less, rugged, integrated cooling.

#### ENERGY EFFICIENT:

Low power consumption.

#### COST-EFFECTIVE:

Competitively priced.

#### FIVE-YEAR WARRANTY:

Comes with a five-year limited warranty and unlimited customer support and service.



## SPECIFICATIONS



## VMWARE® READY

VMware-certified hardware

## MAIN BOARD

Processor: Tera 2321 PCoIP portal processor  
Process: 65nm G-Process CMOS

## MEMORY

System: 512 MB DDR3 (32-bit 667MHz)  
Flash: 256 MB of parallel flash

## GRAPHICS

Max resolution: 2560 x 1600  
Standard resolution: Dual-screen @ 1920 x 1200  
Color: Depth: 8, 15, 16, 24bpp  
Image performance: 150 Mpps  
Max screens: 2

## I/O INTERFACES

Video: 1 x DVI and 1 x DP  
I/O ports: 6 x USB 2.0 (4-front / 2-back)  
Speaker / mic / headphone: 3.5mm Jack

## NETWORKING

Gigabit Ethernet: Ethernet 10/100/1000Mbps – RJ-45

## ENVIRONMENT

Cooling: Fanless – Integrated passive heat sink  
Operating noise: No noise  
Operating temperature: 0°C - ~ 35°C  
Non-operating temperature: -30°C - ~ 60°C  
Operating humidity: 10% - ~ .90% (Non-condensing)  
Non-operating humidity: 5% - ~ 95% (Non-condensing)  
Dimension / weight: 6.8 x 5.2 x 1.1 in / 1.79 lbs  
Locking Port: Integrated Kensington security slot  
Mounting: VESA mount compliant

## AC ADAPTER

Operating voltage range: 100 - ~ 240 VAC  
Rated line frequency: 50 – 60 Hz  
Rated output current (max): 3A  
Output voltage: 12 VDC

## ENERGY

Consumption: 8 W @ idle (36W with 6-USB attached)  
Wake / sleep: Wake on LAN / USB support  
Power failure: Power-on after power-fail

## SOFTWARE

Operating system: O/S independent  
Regulatory: CS, FCC, CE, CCC, C-Tick, KCC, GOST, UL  
Firmware: Free updates available online

